

L Number	Hits	Search Text	DB	Time stamp
1	0	(adjustment with stator with rotor) and injection and screw and mold	USPAT; US-PGPUB	2002/09/27 14:26
2	0	(adjust with stator with rotor) and injection and screw and mold	USPAT; US-PGPUB	2002/09/27 14:26
3	23	((gap or distance) with (frame or housing) with (stator or rotor)) and injection and screw and mold	USPAT; US-PGPUB	2002/09/27 14:32
4	829	((gap or distance) with (adjust or change)) and "linear motor"	USPAT; US-PGPUB	2002/09/27 14:36
5	13	((gap or distance) with (adjust or change)) and "linear motor" and injection and screw and mold	USPAT; US-PGPUB	2002/09/27 14:34
6	109	((gap or distance) with (adjust or change) with magnet\$) and "linear motor"	USPAT; US-PGPUB	2002/09/27 14:37
7	122	((gap or distance) with (adjust or change) with (magnet or magnetic)) and "linear motor"	USPAT; US-PGPUB	2002/09/27 14:38
8	35	((gap or distance) with (adjust or change) with (magnet or magnetic)) and "linear motor") and screw	USPAT; US-PGPUB	2002/09/27 14:38
-	6	emoto.inv. and 425/\$.ccls.	USPAT; US-PGPUB	2002/09/27 14:25
-	1251	((425/149) or (425/150)).CCLS.	USPAT; US-PGPUB	2002/09/25 22:47
-	915	((264/40.7) or (264/328.11)).CCLS.	USPAT; US-PGPUB	2002/09/25 22:46
-	548	((425/149) or (425/150)).CCLS.) and screw	USPAT; US-PGPUB	2002/09/26 16:28
-	457	((264/40.7) or (264/328.11)).CCLS.) and screw	USPAT; US-PGPUB	2002/09/26 17:29
-	81	(linear adj motor) and (425/\$.ccls. or 264/\$.ccls.) and screw	USPAT; US-PGPUB	2002/09/26 18:24
-	83	(425/569).CCLS.	USPAT; US-PGPUB	2002/09/26 18:29
-	277	(425/574).CCLS.	USPAT; US-PGPUB	2002/09/26 18:55
-	221	(injection adj (mold or molding)) and ((magnet or magnetic or electric) with linear) and screw	USPAT; US-PGPUB	2002/09/26 18:58
-	1	("6206683").PN.	USPAT; US-PGPUB	2002/09/27 14:13
-	1	("6206683").PN.) and spring	USPAT; US-PGPUB	2002/09/27 14:14
-	0	(linear adj motor) and (adjust with distance with motor) and (425/\$.ccls. or 264/\$.ccls.)	USPAT; US-PGPUB	2002/09/27 14:15

BEST AVAILABLE COPY